

	724 ZXR 36001	724 QXE 36002	824 QXE 36003
PERFORMANCE			
THROW DISTANCE*	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)
CLEARING WIDTH	24" (61 cm)	24" (61 cm)	24" (61 cm)
AUGER SYSTEM	In-line 2-Stage	In-line 2-Stage	In-line 2-Stage
SNOW CUT DEPTH — 1 PASS	18" (46 cm)	18" (46 cm)	18" (46 cm)
ENGINE			
ENGINE	212cc Toro® OHV	212cc Toro OHV	» 252cc Toro OHV
STARTER	Recoil	» Electric Start	Electric Start
FUEL CAPACITY	2.3 Quarts (2.2 L)	2.3 Quarts (2.2 L)	» 3.4 Quarts (3.2 L)
USER-FRIENDLY FEATURES			
DRIVE SYSTEM	Personal Pace®	Personal Pace	Personal Pace
SPEEDS	Infinitely Variable (0 - 3.5 mph)	Infinitely Variable (0 - 3.5 mph)	Infinitely Variable (0 - 3.5 mph)
AUGER DIAMETER	10"	10"	10"
CHUTE CONTROL	EZ Turn	» Quick Stick®	Quick Stick
TIRES	11" (28 cm) Deep Lug, Directional	11" (28 cm) Deep Lug, Directional	11" (28 cm) Deep Lug, Directional
SCRAPER	Compression Loaded	Compression Loaded	Compression Loaded
WEIGHT	117 lbs. (53 kg)	125 lbs. (57 kg)	131 lbs. (59 kg)
SKIDS	Combination	Combination	Combination
WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited
DEFLECTOR, LOWER CHUTE, CHUTE WARRANTY**	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life



UP TO
30% FASTER
THAN TRADITIONAL
TWO-STAGE
SNOWBLOWERS¹



HANDLES WET, HEAVY SNOW

Tall, open auger housing, free of obstacles reduces clogging in deep snow. The all steel rotor has a (1) helical design which quickly breaks up and gathers snow to the (2) center section that throws snow far through its tall chute opening.



QUICK STICK® CHUTE CONTROL

Innovative joystick control allows you to change chute direction and angle quickly and easily, on the go. (Select models only.)



EZ TURN CHUTE CONTROL

Easily change chute direction with one hand. (Model 36001 only.)



PERSONAL PACE® SELF PROPEL

Toro's innovative Personal Pace® self-propel system automatically senses and adapts to your walking speed.